



Generator Specification

Service	PRP(1)	ESP(2)
Power (KVA)	500	550
Power (KW)	400	440
Rated speed	1500RPM	
Standard voltage	400/230V	
Power factor	0.8	
Phase	3	

Performance Data

Model		GPW500S5 GPW500D5
Engine brand		WEICHAI
Engine model		WP13D490E310
Speed control type		ECU
Alternator brand		GENLITEC
Alternator model		S354G400
Control system		SMARTGEN HGM6120N
Starter motor voltage		24V
Frequency		50Hz
100% Prime Load		110
75% Prime Load		75.3
50% Prime Load		51
25% Prime Load		28
Fuel Tank (L)		860



GENLITEC Power gensets are compliant with ISO 9001 and CE standard, which include the following directives:

- 2006/42/EC Machinery directive
- 2014/30/EU Electromagnetic compatibility directive
- EN 12100:2010; EN ISO 8528-13:2016; EN 60204-1:2018; EN 61000-6-2:2019; EN 61000-6-4:2019
- **GPW500S5 (Silent Type)**
- **GPW500D5 (Open Type)**

(1) PRP (Prime Power)

According to ISO 8528-1, prime power is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during at 24 hours period shall not exceed 80% of the prime power. 10% overload available for governing purposes only.

(2) ESP (Standby Power)


According to ISO 8528-1. It is defined as the maximum power available, under the agreed operating conditions, for which the generating set can deliver for up to 500 hours of operation per year (of which no more than 300 hours for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufactures. No overload capability is available.

Voltage (V)	ESP		PRP		Current Amps
	KVA	KW	KVA	KW	
415/240	550	440	500	400	696
400/230	550	440	500	400	722
380/220	550	440	500	400	760

Standard Reference Conditions

Note: Standard reference condition 25°C (77°F) air inlet temp. 100m (328ft) A.S.L 30% relative humidity. Fuel consumption date with diesel fuel with specific gravity of 0.85 and conforming to BS 2869: 1998 Class A2

Dimension & Weight



Dimension	Open type	Silent type
Length (L)	3150mm	4250mm
Width (W)	1300mm	1500mm
Height (H)	1880mm	2250mm
Net Weight	2830kg	3840kg

Note: This parameter allows for some acceptable deviations.

■ Engine Specification



MODEL: WEICHAH WP13D490E310

Cylinder number	6
Aspiration system	Turbo & aftercooled
Cooling method	Water cooled
Governor type	ECU
Bore x Stroke (mm)	127x165
Compression ratio	15.0:1
Rated speed (RPM)	1500
Displacement (L)	12.54
Rated power (KW)	450
Standby power (KW)	490
Injection	50°C
Coolant capacity (L)	25(engine only)
Oil capacity (L)	30
Fuel system	Common-rail
Starter motor capacity	DC 24V

■ Alternator Specification



MODEL: GENLITEMC S354G400

Number of phase	3
Rated power (KW/KVA)	400/500
Frequency (Hz)	50
Power factor (Cos Phi)	0.8
Poles	4
Temp. rise	125K
Terminals	6/12
Insulation type	H class
Ambient temp.	40°C
IP rating	IP23
Excitation system	Self-excited
Bearing	Single bearing
Coating	Vacuum impregnation
Voltage regulator	A.V.R
Coupling	Flexible disc

Standard Supply Scope

- Industrial exhaust silencer
- Maintenance free battery
- Water cooling radiator
- A.V.R
- Flexible pipes
- Battery wires
- Wiring diagram
- Build-in based fuel tank
- Float Battery charger
- Manual books
- Tool kits
- Emergency stop button
- Base frame
- Digital control panel
- Main circuit breaker

■ Optional Supply Scope

Engine	Alternator	Generator Sets	Control Panel
<input type="checkbox"/> Water jacket pre-heater <input type="checkbox"/> Lubrication oil pre-heater <input type="checkbox"/> Battery isolator	<input type="checkbox"/> Anti-condensation heater <input type="checkbox"/> PMG <input type="checkbox"/> STAMFORD alternator <input type="checkbox"/> LEROY SOMER alternator	<input type="checkbox"/> Extended fuel tank 12h/24h/72h <input type="checkbox"/> Trailer mounted	<input type="checkbox"/> Remote control system <input type="checkbox"/> Build-in/External ATS <input type="checkbox"/> Synchronizing System <input type="checkbox"/> Power output sockets

■ Warranty Period

WEICHAH diesel engine: 12 months or 1000 working hours.

STAMFORD/LEROY SOMER alternator: Global warranty, 12 months or 1000 working hours.

GENLITEMC alternator: Factory warranty, 12 months or 1000 working hours.

DEEPSEA control module: Factory warranty, 12 months or 1000 working hours.

Control Panel

Configuration

- Emergency stop button
- Protection MCB (Main circuit breaker)
- Float battery charger
- ATS connection
- AMF digital control module
- Fuel level meter
- Controller power switch
- Alarm buzzer

Features

- Chinese, English, Spanish, Turkish, Russian & French
- Three phase generator monitoring
- Automatic or manual start/stop of the gensets
- Push buttons for simple control & operation
- Generator measurements (50Hz/60Hz)
- Precision collect & display parameters about ENGINE
- Comprehensive shutdown or warning on fault condition
- Three phase generator protections
 - Over / under voltage
 - Over / under frequency
 - Current / voltage asymmetry
 - Over current / overload
- Three phase AMF function
 - Over / under voltage
 - Loss of phase detection function
- Emergency start function
- IP55 waterproof with rubber-ring gasket



Control Module Model: SMARTGEN HGM6120N

Display	LCD (132 x 64)
Operation panel	Silicon rubber
Digital input	5
Relay output	6
Analogue input	3
AMF	Yes
AC System	1P2W / 2P3W / 3P3W / 3P4W
Alternator voltage	15-360V (ph-N)
Alternator frequency	50/60Hz
KW/Amp Detecting & Display	Yes
Monitor interface	USB
Programmable interface	USB
DC supply	DC 8-35V
Operating temp.	-25 ~ +70°C

Controller Module Options

COMAP	DEIF	DEESEA
AMF25	SGC 420	DSE7320
		

